



POE Ethernet Switch



RAMON



MADE IN IRAN



سوئیچ POE رامون
SNS-P42208BH



SNS-P42208BH

Introduction

12 - Port POE Switch

8 - Port 10/100/1000Base-T(X) POE 2 - Port 10/100/1000Base-T(X) Uplink Port 2 - Port 1000Base-FX(SFP Slot)

Features

- ▶ Support IEEE802.3AF/AT, Support Vlan, 100m Distance
- ▶ Whole Power:120W(52V 2.3A),Internal power supply.
- ▶ All port supported by MDI/MDIX auto flip and self negotiation
- ▶ Supply 8 100/1000 Mbps adaptive high speed forwarding data packet non-lost port.
- ▶ Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.

Specifications

Product	8+2+2 Port SFP POE Switch (Built-in)
Model	SNS-P42208BH
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤120W (52V 2.3A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	24Gbps
Forwarding Mode	Store and forward/Converter mode(9K)
Forwarding Rate	10BASE-T:14880PPS/port , 100BASE-tx:14800pps/port, 1000BASE-tx:1488095pps/port
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT. , POE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10°-- 55°C
Weight	1.15kg
Size	200mm*140mm*44mm(L*W*H)
Warranty	3-years SEPANTA Gold Warranty